

Titan™ 300 Reverse Osmosis System



Titan™ 300 Reverse Osmosis System

- Fully Equipped and Customizable
- Higher Recovery Rates
- Lower Energy Consumption
- High Flow Low-Energy Membranes
- Lower Maintenance
- Compact Space Saving Design
- Individually Wet Tested and Sanitized
- 1-Year Manufacturer's Warranty
- Made in the U.S.A.

Titan Reverse Osmosis Systems feature an excellent pre-treatment design, high quality components and offer high performance. Titan systems are designed for higher recovery rates and minimum energy consumption.

Experience greater savings with lower maintenance and operation costs when you install a Titan Reverse Osmosis System.



Titan 300
1A2002



Titan™ 300 Commercial Reverse Osmosis System

Standard Features:

- **Membrane:** One 2.5" x 21" TFC HF4 Membrane – For maximum rejection of impurities and high flow.
- **Membrane Housing:** One 2.5" x 21" Champ™ Membrane Housing – Features a patented design and requires no tools when servicing.
- **Pump:** Two Aquatec® 8800 Booster Pumps 24 VAC – Designed for continuous use and features built in protection for loss of feed water pressure.
- **Frame:** One Steel White Powder Coated Triple Bracket – Corrosion resistant and light weight.
- **Sediment Filter:** One 2.5" x 20" Slim Line 5 Micron Polypropylene Filter – Removes sediments and protects the system.
- **Carbon Block:** One 2.5" x 20" Slim Line 10 Micron Carbon Block – Removes Chlorine, odor, and taste from the feed water.
- **Sediment Filter:** One 2.5" x 20" Slim Line 1 Micron Polypropylene Filter – Removes sediments and protects the system down to 1 micron.
- **Filter Housing:** Three 2.5" x 20" Slim Line Double O-Ring Filter Housings – Offers durability and improved sealing capabilities.
- **Pressure Gauge:** One PuroTech™ 1.5" 0-160 PSI Pressure Gauge – For accurate monitoring of the system's operating pressure.
- **Tank Switch:** Two Aquatec® Tank Pressure Switches w/ 3/8" JG Ports 20-40 PSI – For automatic operation with a pressure tank.
- **Electronic Shut-Off Valve:** One Aquatec® Electronic 24 Volt Solenoid Valve 3/8" – Automatically shuts off the feed water to the system.
- **Auto-Flush Timer Valve:** One Aquatec® Auto-Flush Timer Valve 700 ml/min 1/4" – Regulates the product to waste ratio (system's recovery) and automatically flushes the membrane on start-up.
- **Transformer:** Two Aquatec® 8800 2 Amp 110 Volt 60 Hertz 24 VAC Transformers. Also available in 220 Volt 50 Hertz.
- **Easy Maintenance & Operation:** Titan™ reverse osmosis systems feature a compact design and have all of their components strategically located for easy access and inspection.

Optional Features:

- **TDS Meter:** One Inline Dual TDS Meter w/ 3/8" Quick Connect Fittings – For monitoring of feed water and product water quality.
- **Stainless Steel Housing:** One 2.5" x 21" PuroTech™ Stainless Steel Membrane Housing 3/8" FNPT.
- **Frame:** One White Steel Frame with Bulk Head Fittings – Can be mounted or free standing.

System Specifications

Model	Titan™ 300	Design	Wall Mount
Gallons Per Day	300 @ 77°F	Dimensions (Approx.)	7" x 28" x 33"
Weight (Approx.)	50 lbs.	Concentrate Re-Circulate	N/A
Auto-Flush	Standard	Element Size (in.)	2521 TFC HF4
Elements (Qty.)	1	Motor HP	N/A
Voltage	110 or 220	Hertz	50 or 60
Feed Connection	3/8"	Product Connection	3/8"
Waste Connection	1/4"		

System Operating Specifications

Minimum Feed Pressure	35 psi
Minimum NaCl % Rejection	96%
Minimum Feed (GPM)	1
Maximum Hardness	15 Grains / Gallon
Maximum TDS	1000 ppm
Operating Pressure	120 psi
Nominal NaCl % Rejection	98.5%
Maximum Feed (GPM)	3
pH Range	3 – 11
Maximum Temperature	105 °F



Titan 300
1A2002
with
Optional Floor
Standing Frame

DISTRIBUTED BY:



541 Industrial Way, Suite 1, Fallbrook, CA 92028
T: (760) 723-5417
F: (760) 728-5062
E: sales@roultratec.com
W: www.roultratec.com